



Detail A
Scale 5:1



Detail B
Scale 5:1



Mould number + Dot code

| INDEX | ZMENY / modifications | DAF | JMENO | SOUHLAS TECHNICKA PT approved | DAF | VIS | TEPIJKA PLENEN | Filing temperature | ≤ 15 °C | NOMINAL OBJEM | Capacity fillpoint | 330 ml ± 7 ml | POZNAMKA | Remarks |
|-------|-----------------------|-----|-------|-------------------------------|-----|-----|-----------------------|--------------------------|-----------|------------------------|------------------------|---------------|-----------------------|-----------------|
| | | | | SOUHVRYTNÍM VYRZM00 | DAF | VIS | TEPIJKA ZPRACOVANI | Conditioning temperature | ≤ 65 °C | TOTAL OBJEM | Capacity brand | 346 ml ± ml | ZAKAZNIK | Customer |
| | | | | VYRZM00 | DAF | VIS | OBSAH CO ₂ | CO ₂ content | ≤ 6 g/l | HMOJNOST | Approx. glass weight | ~ 225 g | PODOBNY JAKO | Similar to |
| | | | | VYRZM00 | DAF | VIS | OBSAH ALKOHOLU | Alcohol content | ≤ 16 Vol% | STREDNI TLOUSTKA STENY | Average wall thickness | 2,44 mm | NAHRAZUJE | Replaces No |
| | | | | | | | AXIALNI ZATIZEN | Axial pressure | dan | PRUJER POUJ USTIM | Neck conection dia | 25 mm | NAHROKA CSLO | Designation |
| | | | | | | | POUZITI | Disposal | MW | AW | EW | X | WITRAL PRUJER KALIBRU | WITRAL Scale |
| | | | | | | | PROCES | Process | BB | PB | EPB | X | BARVA | Color |
| | | | | | | | | | | BR | GR | WIE | | |
| | | | | | | | | | | | | | KRESLICE | Scale |
| | | | | | | | | | | | | | Palm | 11 |
| | | | | | | | | | | | | | DAF | 14.0116 |
| | | | | | | | | | | | | | DMA typ | Filetyp |
| | | | | | | | | | | | | | AZ | |
| | | | | | | | | | | | | | Item No | 5B054_0330_1002 |
| | | | | | | | | | | | | | INDEX | B |

vetropack
 Vetropack Moravia Glass a.s
 CZ-69701 Křivovrh
 Tel: 00420-518 603 111
 www.vetropack.com